



Construction

Brass Body (CuZn38b18)

Finishes

Chrome plated to BS EN 248

Product Type

Contemporary

Water Pressure

Min.0.5 bar, Max. 7.0 bar

Plumbing Systems

Suitable for all plumbing systems, preferably balanced. Min. supply pressure differential requirement is 5:1

Standards

Complies with BSEN 1111

Cartridge

Thermostatic

Fitting

Inlet Connections: 3/4" BSP

Guarantee

10 years against manufacturing faults (3 Years on Serviceable Parts).

Additional Information

1. Stainless steel wall Plate
2. Intergrated shower handset kit
3. Stainless steel 1.5m hose
4. Check valve

Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
	6.7	8.6	10.2	12.7	17.3	20.9	24.0	29.2	33.5	36.0

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.